METHOD AND APPARATUS FOR TRANSMITTING SIGNALS IN A COMMUNICATION SYSTEM

Publication number: JP2001512921 (T)

Publication date: 2001-08-28

Inventor(s):

Applicant(s):

Classification:

- international: ***H04L27/30; H04B7/06; H04B7/10; H04B7/26; H04B15/00; H04J11/00; H04Q7/36;*** **H04L27/26; H04B7/02; H04B7/04; H04B7/26; H04B15/00; H04J11/00; H04Q7/36;** (IPC1-7): H04Q7/36; H04B7/06; H04B7/10; H04B7/26; H04L27/30

- European: H04J11/00; H04B7/06C2D; H04B7/06C3

Application number: JP20000505701T 19980714

Priority number(s): US19970904204 19970731; WO1998US14560 19980714

Also published as:

WO9907090 (A1)
US6038263 (A)
RU2211536 (C2)
EP1228590 (A1)
EP1228590 (A4)

more >>

Abstract not available for JP 2001512921 (T)
Abstract of corresponding document: **WO 9907090 (A1)**

Different orthogonal codes (Wx, Wy) are used to spread common pilot channels (PilotA) intended for transmission to a particular mobile station (106) within a coverage area (sector A) to implement forward link transmit diversity. By implementing separate, different orthogonal codes (Wx, Wy) for each pilot channel (PilotA), the pilot signals transmitted via antennas (218, 222) to a common coverage area (sector A) are orthogonal to one another and thus do not degrade system performance. Additionally, the use of different orthogonal codes (Wx, Wy) for each pilot channel (PilotA) allows the mobile station (106) to discern which pilot channel spread with a different orthogonal code includes corresponding traffic channel (TCH) information. This allows forward link transmit diversity to be enabled/disabled based on conditions associated with the environment, the communications channel, etc. without a complete loss of information as seen by the mobile station (106).